

High pressure cleaner

Hot water, mobile, oil heated - series Etronic II HD1140 Tel: 01748 826 200

Email: sales@tandjcleaningequipment.co.uk






























Туре		HD1140-Standard	HD1140-Premium	
Operating pressure Max. pressure Discharge capacity Nozzle size Hot water capacity Pump speed Connected load 7 Electrical protection 3x	3/400-415V/ 50Hz 30-230bar/ 3-23MPa 250bar/ 25MPa 00 - 1000l/h 045 0 - 98°C (150°C) 1400rpm ,6kW / 14,1A (16A slow-blowing	 Etronic II - Controls 10m HP-Hose DN08 - 315bar Trigger-Gun with swivel Spray-Lance 900mm c/w Nozzle-Protection Stainless-Steel Jet-Nozzle 25° Water-Supply separation acc. water reg. Chemical supply in high-pressure Jet c/w Metering-valve 	 Etronic II - Controls Hose-Reel 20m HP-Hose DN08 - 315bar Trigger-Gun with swivel Spray-Lance 900mm c/w Nozzle- Protection Stainless-Steel Jet-Nozzle 25° Spray-Lance 900mm c/w Rotary-Nozzle Water-Supply separation acc. water reg. Chemical supply in high-pressure Jet c/w Metering-valve 	
Weight net / with package		178 kg / 199 kg	187 kg / 208 kg	
Dimensions device / with package (LxWxH)		1070x735x1020mm/1160x770x960mm 1070x735x1310mm/1160x770x1350mm		

Robust, corrosion-resistant, self-supporting device chassis, impact-resistant device-cover made of ABS, triplex-piston pump wit h brass pump head, nickel plated, high-performance ceramic piston, stainless-steel valves, leakage-return, Etronic II - controls: (Start-stop syst em with switch-off delay, total-switch-off after 20min, OPH-counter with service information, low-water cut-off, low-fuel cut-off, optical flame monitoring with photoelectric cell and fault indicator-light, steam-stage) 2 motors system (independent of the direction of rotation) separately for H.P.-Pump and heating, unloader safety-valve c/w Infinitely variable pressure and quantity regulation, 4 large rubber wheels for rough terrain, with a patented wheel brake 2-way, storage possibility for all accessories, integrated diesel-tank 25I, integrated detergent-tank 20I, robust rotary on-off switch, 7,5m connection cable, removable ergonomic drawbar

Art. N	lo.	410001	410002