

High pressure cleaner

Cold water, mobile - series 4x4 KD1140 Tel: 01748 826 200

Email: sales@tandjcleaningequipment.co.uk























| Туре | | KD1140-Standard | KD1140-Premium |
|-------------------------------------------------|---------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------|
| Voltage Operating pressure | 3/400-415V/ 50Hz 30-250bar/ 3-25MPa 270bar/ 27MPa | ▶ Trigger-Gun with swivel ▶ 15 ▶ Spray-Lance 900mm c/w Vario-Nozzle ▶ Sp ▶ Stainless-Steel Jet-Nozzle 25° ▶ Pro | Hose-Reel 15m HP-Hose DN08 - 315bar Trigger-Gun with swivel |
| Max. pressure Discharge capacity 3 Nozzle size | 00 - 1.000l/h 045 | | ➤ Spray-Lance 900mm c/w Nozzle- Protection ➤ Stainless-Steel Jet-Nozzle 25° |
| Max. Inlet temperature 45°C Pump speed 1400rpm | | Detergent-Supply c/w Low-Pressure Injector and metering-valve | Spray-Lance 900mm c/w Rotary-Nozzle17I Water-Storage tank |
| Connected load 7 | 7,4kW / 13,1A x16A slow-blowing | | Water-Supply separation acc. water reg. Chemical supply in high-pressure Jet c/w Metering-valve |
| Weight net / with package | | 89 kg / 113kg | 97 kg / 121 kg |
| Dimensions device / with package (LxWxH) | | 980 x 620 x 1000 mm / 1050 x 760 x 1180 mm | 1020x620x1000mm/1050x760x1180mm |

Self-supporting, robust, rotation-moulded device-chassis, impact-resistant device-cover made of ABS, triplex-piston pump with brass pump head, nickel-plated, high-performance ceramic piston, stainless-steel valves, leakage-return, start-stop system with switch-off delay, total-switch-off after 20min, unloader safety-valve c/w Infinitely variable pressure and quantity regulation, 4 large rubber wheels for rough terrain, with a patented wheel brake 2-way, storage possibility for all accessories, robust rotary on-off switch, 7,5m connection cable, removable ergonomic drawbar

| Art. No. | 551001 | 551002 | | |
|----------|--------|--------|--|--|