

## High pressure cleaner

Cold water, mobile - series 4x4 KD1340

Tel: 01748 826 200

Email: sales@tandjcleaningequipment.co.uk























Туре		KD1340-Standard	KD1340-Premium
Voltage	3/400-415V/ 50Hz	▶ 10m HP-Hose DN08 - 315bar	► Hose-Reel
Operating pressure	30-170bar/ 3-17MPa	<ul> <li>Trigger-Gun with swivel</li> <li>Spray-Lance 900mm c/w Vario- Nozzle</li> </ul>	<ul> <li>15m HP-Hose DN06 - 315bar</li> <li>Trigger-Gun with swivel</li> <li>Spray-Lance 900mm c/w Nozzle- Protection</li> <li>Stainless-Steel Jet-Nozzle 25°</li> </ul>
Max. pressure	190bar/ 19MPa		
Discharge capacity 3	00 - 1.300l/h	Stainless-Steel Jet-Nozzle 25°	
Nozzle size	070	► 25l Cleaning-Detergent tank	
Max. Inlet temperature 45°C		► Detergent-Supply c/w Low-Pressure	► Spray-Lance 900mm c/w Rotary-Nozzle
Pump speed	1400rpm	Injector and metering-valve	<ul> <li>17l Water-Storage tank</li> <li>Water-Supply separation acc. water reg.</li> <li>Chemical supply in high-pressure Jet c/w Metering-valve</li> </ul>
Connected load	,4kW / 13,1A		
Electrical protection 3	x16A slow-blowing		
Weight net / with package		89 kg / 113 kg	97 kg / 121 kg
Dimensions device / with package (LxWxH)		980 x 620 x 1000 mm / 1050 x 760 x 1180 mm	1020 x 620 x 1000 mm / 1050 x 760 x 1180 mm

Self-supporting, robust, rotation-moulded device-chassis, impact-resistant device-cover made of ABS, triplex-piston pump with brass pump head, nickel-plated, high-performance ceramic piston, stainless-steel valves, leakage-return, start-stop system with switch-off delay, total-switch-off after 20min, unloader safety-valve c/w Infinitely variable pressure and quantity regulation, 4 large rubber wheels for rough terrain, with a patented wheel brake 2-way, storage possibility for all accessories, robust rotary on-off switch, 7,5m connection cable, removable ergonomic drawbar

Art. No.	552001	552002