



High pressure cleaner

Cold water, mobile - series 3x3

KD623



Type	KD623-Standard		KD623-Premium
Voltage	1/ 230V/ 50Hz		
Operating pressure	30-160bar/ 3-16MPa		
Max. pressure	180bar/ 18MPa		
Discharge capacity	300 - 600 l/h		
Nozzle size	034		
Max. Inlet temperature	45°C		
Pump speed	1400rpm		
Connected load	2,9kW / 14,2A		
Electrical protection	16A slow-blowing		
	<ul style="list-style-type: none"> ▶ 10m HP-Hose DN06 - 250bar ▶ Trigger-Gun with swivel ▶ Spray-Lance 900mm c/w Vario-Nozzle ▶ Stainless-Steel Jet-Nozzle 25° ▶ 15l Cleaning-Detergent tank ▶ Detergent-Supply c/w Low-Pressure Injector and metering-valve 		<ul style="list-style-type: none"> ▶ Hose-Reel ▶ 15m HP-Hose DN06 - 250bar ▶ Trigger-Gun with swivel ▶ Spray-Lance 900mm c/w Nozzle-Protection ▶ Stainless-Steel Jet-Nozzle 25° ▶ Spray-Lance 900mm c/w Rotary-Nozzle ▶ 17l Water-Storage tank ▶ Water-Supply separation acc. water reg. ▶ Chemical supply in high-pressure Jet c/w Metering-valve
Weight net / with package	46 kg / 66 kg		50 kg / 70 kg
Dimensions device / with package (LxWxH)	805 x 485 x 950 mm / 790 x 595 x 810 mm		830 x 485 x 950 mm / 790 x 595 x 810 mm
<p>Self-supporting, robust, rotation-moulded device-chassis, impact-resistant device-cover made of ABS, triplex-piston pump with brass pump head, nickel plated, high-performance ceramic piston, stainless-steel valves, leakage-return, start-stop system with switch-off delay, total-switch-off after 20min, unloader safety-valve c/w infinitely variable pressure and quantity regulation, 2 large rubber wheels for rough terrain with rubber stand, storage possibility for all accessories, robust rotary on-off switch, 5,0m connection cable, removable ergonomic drawbar</p>			
Art. No.	558001		558002