

High pressure cleaner

Cold water, mobile - series 3x3

KD823

Tel: 01748 826 200

Email: sales@tandjcleaningequipment.co.uk



Type	KD823-Standard		KD823-Premium	
Voltage	1/ 230V/ 50Hz		▶ Hose-Reel	
Operating pressure	30-140bar/ 3-14MPa		▶ 15m HP-Hose DN08 - 315bar	
Max. pressure	165bar/ 16,5MPa		▶ Trigger-Gun with swivel	
Discharge capacity	300 - 720l/h		▶ Spray-Lance 900mm c/w Vario-Nozzle	
Nozzle size	045		▶ Spray-Lance 900mm c/w Nozzle-Protection	
Max. Inlet temperature	45°C		▶ Stainless-Steel Jet-Nozzle 25°	
Pump speed	1400rpm		▶ 15l Cleaning-Detergent tank	
Connected load	3,2kW / 14,7A		▶ Detergent-Supply c/w Low-Pressure Injector and metering-valve	
Electrical protection	16A slow-blowing		▶ Water-Supply separation acc. water reg.	
Weight net / with package	51,8 kg / 71,8 kg		▶ 17l Water-Storage tank	
Dimensions device / with package (LxWxH)	805 x 485 x 950 mm / 790 x 595 x 810 mm		▶ Water-Supply separation acc. water reg.	
			▶ Chemical supply in high-pressure Jet c/w Metering-valve	
Art. No.	562001		562002	

Self-supporting, robust, rotation-moulded device-chassis, impact-resistant device-cover made of ABS, triplex-piston pump with brass pump head, nickel plated, high-performance ceramic piston, stainless-steel valves, leakage-return, start-stop system with switch-off delay, total-switch-off after 20min, unloader safety-valve c/w infinitely variable pressure and quantity regulation, 2 large rubber wheels for rough terrain with rubber stand, storage possibility for all accessories, robust rotary on-off switch, 5,0m connection cable, removable ergonomic drawbar