

Cold Pressure Washer MLC-C 1813P T 400/50

Order code: PPEL40058

The MLC-C is a range of professional models ready to use in most segments due to 1450/2800 rpm motors. The MLC-C offers powerful cleaning, high durability and low noise level.



Easy to use

MLC-C is a simple, basic machine. All models are delivered without cabinet



Easy to install

All machines are equipped with a painted metal plate for wall-mounting



Pump with brass head

New Ipc H.P. plunger pump with brass head and three ceramic pistons, for a long working life

**Great performance
ready to use**



IPC

Technical Specifications

Operating pressure	bar	30÷180
Volume	l/h	800
Inlet water temp.	°C	50
Pressure and steam phase regulation		-

Electrical Features

Power supply	Ph/V/Hz	3/400/50
Absorbed power	kW	5,1
Motor pole	rpm	2 - 2800
Remote control		By-pass
Dry running control		No
Microleaks control		No
Signal pilot for fuel, detergent and anti-scale lack		No

Hydraulic Features

Pump		IPC plunger
Pump head		Brass
Pistons type		Full ceramic
Detergent tank	l	-
Detergent delivery		-
Antiscale device		No
Descaling tank		No

Termal Features

Boiler type		-
Coil		-
Burner power		-
Fuel consumption (full temp/ecoselect mode)		-
Fan motor		-
Fuel tank		-

Dimension & Weight

Weight	Kg	49
Dimension (LxWxH)	cm	60x48x32
Frame structure		Painted metal plate
Version		-

Packaging

Type		Carton
Dimensions (LxWxH)	cm	60X55X40
Volume	m³	0,49
Weight	Kg	-
Complete pallet quantity	pcs	-

Equipment (on request)

IPIP40006	Handgrip	G5100
TBAP25324	High pressure hose	R1 10 m 5/16
LCLC40004	Lance	Lance Inox 70 cm
UGLN49987	High pressure nozzle	H.P.15°

Optional Accessories

-	Turbo nozzle
-	Hose reel
-	Rotating hydro brush
-	Fixed hydro brush lance
LCPR40039	Foam head
-	Feeding kit
-	Lance for washing floors
-	Drain kit
-	Plunger ejectore device
RCIN10810	Hose couplings



Ip Cleaning S.p.A.
Viale Treviso 63
30026 Summaga di Portogruaro
(VE) / ITALY

Tel. ++39 0421 205511
Fax ++39 0421 204227

info@ipcleaning.com
www.ipcleaning.com