

High pressure cleaner

Hot water, mobile, oil heated - series Etronic I HD 640 Tel: 01748 826 200

Email: sales@tandjcleaningequipment.co.uk


























Туре		HD640-Standard	HD640-Premium	
Voltage Operating pressure Max. pressure Discharge capacity Nozzle size Hot water capacity Pump speed Connected load Electrical protection	3/400-415V/50Hz 30-180bar/3-18MPa 200bar/20MPa 300 - 600I/h 034 30 - 98°C 1400rpm 4,6kW/8,0A 3x16A slow-blowing	 Etronic I - Controls 10m HP-Hose DN08 - 315bar Trigger-Gun with swivel Spray-Lance 900mm c/w Nozzle- Protection Stainless-Steel Jet-Nozzle 25° Water-Supply separation acc. water reg. Chemical supply in high-pressure Jet c/w Metering-valve 	 Etronic I - Controls Hose-Reel 20m HP-Hose DN08 - 315bar Trigger-Gun with swivel Spray-Lance 900mm c/w Nozzle- Protection Stainless-Steel Jet-Nozzle 25° Spray-Lance 900mm c/w Rotary-Nozzle Water-Supply separation acc. water reg. Chemical supply in high-pressure Jet c/w Metering-valve 	
Weight net / with package		157 kg / 178 kg	167 kg / 187 kg	
Dimensions device / with package (LxWxH)		1070 x 735 x 1020 mm / 1160 x 770 x 960 mm	1070 x 735 x 1310 mm / 1160 x 770 x 1350 mm	

Robust, corrosion-resistant, self-supporting device chassis, impact-resistant device-cover made of ABS, triplex-piston pump wit pump head, nickel plated, high-performance ceramic piston, stainless-steel valves, leakage-return, Etronic I - controls: (Start with switch-off delay, total-switch-off after 20min) 2 motors system (independent of the direction of rotation) separately for H.P.-Pump and heating, unloader safety-valve c/w infinitely variable pressure and quantity regulation, 4 large rubber wheels for rough terrain, with a patented wheel brake 2-way, storage possibility for all accessories, integrated diesel-tank 25l, integrated detergent-tank 20l, robust rotary on-off switch, 7,5m connection cable, removable ergonomic drawbar

h brass -stop system

Art. No.	412001	412002