

High pressure cleaner

Cold water, mobile - series 4x4 KD1840 Tel: 01748 826 200

Email: sales@tandjcleaningequipment.co.uk























Туре		KD1840-Premium	
Voltage 3	3/400-415V/ 50Hz	► Hose-Reel	
Operating pressure 3	30-120bar/ 3-12MPa	 15m HP-Hose DN10 - 315bar Trigger-Gun with swivel Spray-Lance 900mm c/w Nozzle- Protection 	
Max. pressure 1	40bar/ 14MPa		
Discharge capacity 300 - 1.800l/h		Stainless-Steel Jet-Nozzle 25°	
Nozzle size 1	50	► Spray-Lance 900mm c/w Rotary-Nozzle	
Max. Inlet temperature 45°C		► 17l Water-Storage tank	
Pump speed 1	400rpm	 Water-Supply separation acc. water reg. Chemical supply in high-pressure Jet c/w Metering-valve 	
Connected load 7,4	łkW / 13,1A	a certifical supply in high pressure see QVI Metering Valve	
Electrical protection 3x1	6A slow-blowing		
Weight net / with package		105 kg / 129 kg	
Dimensions device / with package (LxWxH)		1020x620x1000mm/1050x760x1180mm	

Self-supporting, robust, rotation-moulded device-chassis, impact-resistant device-cover made of ABS, triplex-piston pump with brass pump head, high-performance ceramic piston, stainless-steel valves, leakage-return, start-stop system with switch-off delay, total-switch-off after 20min, unloader safety-valve c/w Infinitely variable pressure and quantity regulation, 4 large rubber wheels for rough terrain, with a patented wheel brake 2-way, storage possibility for all accessories, robust rotary on-off switch, 7,5m connection cable, removable ergonomic drawbar

Art. No.	563002
AIL NO.	303002