

## High pressure cleaner

Hot water, mobile, oil heated wih engine series HDB - HDB1540

Tel: 01748 826 200

Email: sales@tandjcleaningequipment.co.uk















d		ŀ
		Ų,
		+

Туре		HDB1540-Standard	HDB1540-Premium
Nozzle size Hot water heating 30 Pump speed Connected load 1	Gasoline 30-280bar/ 3-28MPa 300bar/ 30MPa 00 - 1000l/h 034 0 - 98°C 1400rpm 8h.p. B&S Option	<ul> <li>10m HP-Hose DN08 - 315bar</li> <li>Trigger-Gun with swivel</li> <li>Spray-Lance 900mm c/w Nozzle- Protection</li> <li>Stainless-Steel Jet-Nozzle 25°</li> <li>Water-Supply separation acc. water reg.</li> <li>Chemical supply in high-pressure Jet c/w Metering-valve</li> </ul>	<ul> <li>Hose-Reel</li> <li>20m HP-Hose DN08 - 315bar</li> <li>Trigger-Gun with swivel</li> <li>Spray-Lance 900mm c/w Nozzle- Protection</li> <li>Stainless-Steel Jet-Nozzle 25°</li> <li>Spray-Lance 900mm c/w Rotary-Nozzle</li> <li>Water-Supply separation acc. water reg.</li> <li>Chemical supply in high-pressure Jet c/w Metering-valve</li> </ul>
Weight net / with package		206 kg / 234 kg	215 kg / 243 kg
Dimensions device / with package (LxWxH)		1200 x 800 x 800 mm / 1210 x 810 x 960 mm	1200x800x800mm/1210x810x1350mm

Robust, corrosion-resistant, self-supporting device chassis, impact-resistant device-cover made of steel galvanized and powder-coa ted, triplex-piston pump with brass pump head, high-performance ceramic piston, stainless-steel valves, leakage-return, gearbox reducing the high-pressure pump speed, separately driven burner motor for heating, 4-fold safety system, consisting of pressure unloader safety-valve c/w Infinitely variable pressure and quantity regulation, safety-valve and thermostat, automatic load-idle control, 4 large ruber-pneumatic tires for rough terrain, storage possibility for all accessories, removable standard diesel-canister 20l, external 2-way detergent supply, removable ergonomic drawbar

for -switch, speed

Art. No.	164001	164002		
Art. No. device with electric-starter	165001	165002 €		