

High pressure cleaner

Hot water, mobile, oil heated wih engine
series HDB - HDD1240

Tel: 01748 826 200

Email: sales@tandjcleaningequipment.co.uk



Type		HDD1240-Standard	HDD1240-Premium
Engine	Diesel	<ul style="list-style-type: none"> ▶ 10m HP-Hose DN08 - 315bar ▶ Trigger-Gun with swivel ▶ Spray-Lance 900mm c/w Nozzle- Protection ▶ Stainless-Steel Jet-Nozzle 25° ▶ Water-Supply separation acc. water reg. ▶ Chemical supply in high-pressure Jet c/w Metering-valve ▶ With electric-starter 	<ul style="list-style-type: none"> ▶ Hose-Reel ▶ 20m HP-Hose DN08 - 315bar ▶ Trigger-Gun with swivel ▶ Spray-Lance 900mm c/w Nozzle- Protection ▶ Stainless-Steel Jet-Nozzle 25° ▶ Spray-Lance 900mm c/w Rotary-Nozzle ▶ Water-Supply separation acc. water reg. ▶ Chemical supply in high-pressure Jet c/w Metering-valve ▶ With electric-starter
Operating pressure	30-180bar/ 3-18MPa		
Max. pressure	200bar/ 20MPa		
Discharge capacity	300 - 1000l/h		
Nozzle size	050		
Hot water heating	30 - 98°C		
Pump speed	1400rpm		
Connected load	10h.p. Diesel Yanmar		
Electric-Starter	Starter-Generartor		
Weight net / with package		238 kg / 251 kg	246 kg / 259 kg
Dimensions device / with package (LxWxH)		1200x800x735 mm / 1210x810x1160 mm	1200x800x1005 mm / 1210x810x1350 mm
<p>Robust, corrosion-resistant, self-supporting device chassis, impact-resistant device-cover made of steel galvanized and powder-coated, triplex-piston pump with brass pump head, high-performance ceramic piston, stainless-steel valves, leakage-return, gearbox reducing the high-pressure pump speed, separately driven burner motor for heating, 4-fold safety system, consisting of pressure unloader safety-valve c/w Infinitely variable pressure and quantity regulation, safety-valve and thermostat, automatic load-idle speed control, 4 large rubber-pneumatic tires for rough terrain, storage possibility for all accessories, removable standard diesel-canister 20l, external 2-way detergent supply, removable ergonomic drawbar</p>			
Art. No.		158001	158002

for
-switch,