


High pressure cleaner

Cold water, stationary - series KS

KS823 - hot water resistant



INOX

Type	KS823	KS823-INOX
Voltage	1/ 230V / 50Hz	
Operating pressure	30-120bar/ 3-12MPa	
Max. pressure	140bar/ 14MPa	
Discharge capacity	300 - 720l/h	
Nozzle size	050	
Max. Inlet temperature	80°C	
Pump speed	1400rpm	
Connected load	2,6kW / 12,8A	
Electrical protection	16A träge	
Weight net / with package	102 kg/ 116 kg	102 kg/ 116 kg
Dimensions device / with package (LxWxH)	780 x 510 x 540 mm / 1200 x 800 x 700 mm	780 x 510 x 540 mm / 1200 x 800 x 700 mm
<p>Self-supporting, robust, device-chassis made from galvanized steel and powder-coated (option INOX: device-chassis made out of stainless-steel), wall-bracket, drawable technic-tablar on telescopic rails, triplex-piston pump with brass pump head, hot-water resistant up to 80°C, high-performance ceramic piston, stainless-steel valves, leakage-return, start-stop system with switch-off delay, total-switch-off after 20min with leakage-recognition, unloader safety-valve c/w Infinitely variable pressure and quantity regulation, robust rotary on-off switch, 7,5m connection cable</p>		
Art. No.	157	157000